



# Express 6540 Series

## SHDSL 2-wire/4-wire Network Termination Unit (NTU)

### Product Features

- Interface between the SHDSL network and the user's DTE
- 2-wire or 4-wire SHDSL network connection
- G.703 and/or Nx64k customer ports compliant with V.35, V.36, X.21, V.28, V.10, V.11, and V.24 ITU-T recommendations
- Four recessed pushbuttons for easy operation along with eight LEDs signifying operational functionality
- Tabletop unit
- Rackmount capability in the ADTRAN Express shelf that can hold seven units
- Three varied power schemes: local AC, local DC, and span-powered with local DC power auto-switchover
- Three management options: local VT100, remote VT100, remote Network Management System
- RoHS Compliant
- Industry-leading warranty

**As symmetric data usage in networks increases, efficient Symmetric High Bit Rate Digital Subscriber Line (SHDSL) equipment is required in both the local loop and at the customer premises.** The ADTRAN® Express 6540® SHDSL 2-wire/4-wire NTU Series provides the interface between the SHDSL network and the user's Data Terminal Equipment (DTE) for applications such as LAN-to-LAN bridging, Frame Relay circuit, and PABX termination.

The Express 6540 Series operates in two different system configurations:

- As a remote unit to the ADTRAN Total Access® 3000 multiservice platforms
- In pairs as a point-to-point limited distance campus configuration

The Express 6540 Series supports the following customer interfaces and operations:

- A Nx64k single service interface with a data transmission rate of 64 kbps to 2.304 Mbps in 2-wire mode (N x 64 kbps, where N=1 to 36) or 64 kbps to 4.608 Mbps in 4-wire mode (N x 64 kbps, where N=1 to 72)
- A G.703 interface with G.704 framing, with single or multiple G.703 services with a data transmission rate from 64 kbps to 1.984 Mbps (N x 64 kbps, where N=1 to 31)
- The G.703 interface with G.704 framing will run over SHDSL in aligned mode and support simultaneous services using the Nx64k port for the second service
- A G.703 interface without framing, providing a single 2.048 Mbps service (N x 64 kbps, where N=1 to 32)

The Express 6540 Series is housed in a standalone plastic case available in AC, DC, or SHDSL span/DC powered models. The front panel provides pushbuttons for operation of local and remote port loopbacks and built-in BERT testing, and has LED status indicators for data port, loopback, and BERT conditions. The front and rear panels have been designed to accommodate specific product model requirements, including four recessed pushbuttons and eight LED indicators for the front panel, and SHDSL, G.703 and/or Nx64k customer ports, local management port, and a local power connection for the rear panel. The Express 6540 Series has the capability of being fully configured and managed by:

- A local VT100 management port
- A remote VT100 virtual terminal session via the Total Access 3000 SCU management port
- Remote NMS using the SHDSL EOC and SNMP proxy by Total Access 3000 LTU





ADTRAN, Inc.  
Global Department  
901 Explorer Boulevard  
Huntsville, Alabama 35806  
USA  
[www.adtran.com/global](http://www.adtran.com/global)

**U.S. Headquarters**  
+1 256 963 8000  
+1 256 963 6300 fax  
[international@adtran.com](mailto:international@adtran.com)

**Global Customer Service**  
+1 256 963 8716 voice

**Asia—Beijing, China**  
+86 10 8527 5011  
+86 10 8527 5010 fax  
[sales.china@adtran.com](mailto:sales.china@adtran.com)

**Hong Kong**  
+852 3187 7111  
+852 2116 4084 fax  
[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

**Asia—Bangkok, Thailand**  
+66 2 610 3724  
+66 2 610 3601 fax  
[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

**Asia—Singapore**  
+65 6232 2305  
+65 6232 2888 fax  
[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

**Australia/New Zealand—  
Melbourne, Australia**  
+61 3 9658 0500  
+61 3 9658 0599 fax  
[sales.australia@adtran.com](mailto:sales.australia@adtran.com)

**Australia/New Zealand—  
Sydney, Australia**  
+61 2 8456 0101  
+61 2 8456 0105  
[sales.australia@adtran.com](mailto:sales.australia@adtran.com)

**Canada—Montreal, Quebec**  
+1 877 923 8726  
+1 514 940 2888  
+1 514 989 3198 fax  
[sales.canada@adtran.com](mailto:sales.canada@adtran.com)

**Canada Headquarters—  
Toronto, Ontario**  
+1 877 923 8726  
[sales.canada@adtran.com](mailto:sales.canada@adtran.com)

**EMEA Regional Headquarters—  
United Kingdom**  
+44 1256 884055  
+44 1256 884056 fax  
[sales.emea@adtran.com](mailto:sales.emea@adtran.com)  
[sales.europe@adtran.com](mailto:sales.europe@adtran.com)

**Mexico/Central America/  
Caribbean—USA**  
+1 256 963 4833  
+1 256 963 6300 fax  
[sales.latin@adtran.com](mailto:sales.latin@adtran.com)  
[sales.caribbean@adtran.com](mailto:sales.caribbean@adtran.com)  
[sales.mexico@adtran.com](mailto:sales.mexico@adtran.com)  
[sales.ai@adtran.com](mailto:sales.ai@adtran.com)

**South America—USA**  
+1 256 963 3113  
+1 256 963 6300 fax  
[sales.latin@adtran.com](mailto:sales.latin@adtran.com)  
[sales.brazil@adtran.com](mailto:sales.brazil@adtran.com)  
[sales.ai@adtran.com](mailto:sales.ai@adtran.com)



TL19:1270



ADTRAN is an ISO 9001, ISO 14001,  
and a TL 9000 certified supplier.

I-61230001L1-8B March 2009  
Copyright © 2009 ADTRAN, Inc.  
All rights reserved.

# Express 6540 Series

## SHDSL 2-wire/4-wire Network Termination Unit

## Product Specifications

### Front Panel Features

#### Recessed Pushbuttons

- Port Select
- Local Loop/ERR INJ
- Remote Loop
- BERT

#### Tri-Color LEDs

- SHDSL
- G.703
- Nx64k
- RTS/C
- RLSD/I
- LLOOP
- RLOOP
- BERT

### Mechanical

- **Dimensions:** 5.3 cm H x 23.6 cm W x 16.8 cm D
- **Weight:** Less than 1 kg
- **Mounting:** Seven units can be mounted in one ADTRAN Express Shelf

### Interfaces

#### Network Interface

- SHDSL, 2- or 4-wire

#### Subscriber Interface

- G.703
- Nx64k
- V.35
- V.36
- X.21
- V.28
- V.10
- V.11
- V.24

### Electrical

#### Power Requirements AC Models

- 100–240 VAC, 50/60 Hz, 100 mA

#### Power Requirements DC Models

- -32 to -80 VDC, -48 V nominal

### Regulatory Standards

- CE Mark
- A-tick (Australia)
- ETL registered
- FCC Class B
- RoHS Compliant

### Management

- **Local Management:** VT100
- **Remote Management:** VT100 Virtual Terminal via Total Access 3000 LTU or Remote NMS using EOC and SNMP proxy by Total Access 3000 LTU

### Environmental

- **Operating:** -5°C to +55°C
- **Storage:** ETS 300 019-2-1 Class 1.2
- **Relative Humidity:** Up to 90 percent, noncondensing

## Ordering Information

Equipment	Part #
Express 6540 SHDSL 2w/4w NTU, AC	1230001E1
Express 6540 SHDSL 2w/4w NTU, DC	1230002E1
Express 6541 SHDSL 2w/4w NTU, AC	1230007E1
Express 6541 SHDSL 2w/4w NTU, DC	1230008E1
Express 6542 SHDSL 2w/4w NTU, E1 SPN/DC	1230009E1



Express 6540 AC



Express 6540 DC



Express 6541 AC



Express 6541 DC



Express 6542 Span or DC

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN, NetVanta, and Total Access are registered trademarks of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. Five-year warranty applies only to products sold in North America.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exporticence](http://www.adtran.com/exporticence)